

# Prevail™ 4000

TWO-PART EPOXY (PART B)

### **SECTION 1: IDENTIFICATION**

Product name: Prevail 4000 Two-Part Epoxy (Part B)

Synonyms: None

**Product use description:** Flooring Adhesive

**Company:** 

Metroflor® Corporation 119 Thomas St. Calhoun, GA 30701 (888) 235-6672

Emergency contact: Chemtrec (800) 424-9300

## **SECTION 2: HAZARD(S) IDENTIFICATION**

#### Classification:

Skin Corr. 1B H314
Eye Dam. 1 H318
Skin Sens. 1 H317
Aquatic Chronic 2 H411

Refer to Section 16 for full text of H-Phrases

### **Hazard Pictograms:**



GHS05





Signal Word: Danger

### **Hazard statements:**

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H411 - Toxic to aquatic life with long lasting effects.

#### **Precautionary statements:**

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 – IF ON SKIN (OR HAIR): Take of immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 – IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a poison center or doctor.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 – Store locked up.

P501 – Dispose of contents/container in accordance with local, regional, national, and international regulations.

Other hazards: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown acute toxicity: No data available

Section 3: Composition/Information on Ingredients\*

Component	CAS-No.	Weight %	Classification
Father aids 040 march material discount	68082-29-1	15-40	Skin Irrit. 2, H315
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and			Eye Dam. 1, H318
triethylenetetramine			Skin Sens. 1, H317
and the state of t			Aquatic Chronic 2, H411
Propanol, oxybis-, dibenzoate	27138-31-4	3-7	Aquatic Chronic 3, H412
	90-72-2	3-7	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
2.4.6 Tri/dimethyleminemethyl) phonel			Skin Corr. 1B, H314
2,4,6-Tri(dimethylaminomethyl) phenol			Eye Dam. 1, H318
			Skin Sens. 1, H317
			Aquatic Chronic 3, H412
	112-57-2	3-7	Skin Corr. 1B, H314
   Tetraethylenepentamine			Skin Sens. 1, H317
retraethylenepentamme			Aquatic Acute 3, H402
			Aquatic Chronic 2, H411
	112-24-3	1-5	Acute Tox, 3 (Dermal), H311
			Skin Corr. 1B, H314
  Triethylenetetramine			Eye Dam. 1, H318
			Skin Sens. 1, H317
			Aquatic Acute 3, H402
			Aquatic Chronic 3, H412
	14808-60-7	0.1-1.0	Carc. 1A, H350
Quartz**			STOT SE 3, H335
			STOT RE 1, H372

<sup>\*</sup>The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

### **SECTION 4: FIRST-AID MEASURES**

**General**: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Eye contact:** Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Skin contact:** Immediately flush skin with plenty of water for at least 60 minutes. Take off contaminated clothing and wash it before reuse. Call a POISON CENTER or doctor/physician if you feel unwell.

**Inhalation**: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Effects of Overexposure: Causes severe skin burns and eye damage. May cause an allergic reaction in sensitive individuals.

Eyes: Serious damage to eyes. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Skin:** Contact may cause immediate severe irritation progressing quickly to chemical burns. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic reaction in sensitive individuals.

<sup>\*\*</sup>Finely divided Quartz dust has caused cancer and lung disease in workers that inhale it over an extended period of time. Since this product is in a liquid form, the Quartz dust is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with Quartz dust are not applicable to this product.

Full text of H-phrases: see Section 16

# **SECTION 4: FIRST-AID MEASURES (CONTINUED)**

Ingestion: Ingestion is likely to be harmful or have adverse effects.

**Inhalation:** May cause respiratory irritation. **Chronic symptoms:** No data available.

Notes to physician: Show label where possible

### **Section 5: Fire-Fighting Measures**

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### Specific hazards from substance/mixture:

**Fire hazard:** Product is not flammable. **Explosion hazard:** Product is not explosive.

Reactivity: Hazardous polymerization can occur on heating.

#### Specific hazards during fire fighting:

**Precautionary measures fire:** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

**Firefighting instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Hazardous combustion products:** Under fire conditions this material may produce hazardous carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides. Amines. Ammonia.

**Special protective equipment for fire-fighters**: Do not enter fire area without proper protective equipment, including respiratory protection.

Further information: Refer to Section 9 for flammability properties.

### Section 6: Accidental Release Measures

### Personal precautions:

**General measures:** Do not breathe vapor, mist, or spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Do not allow product to spread into the environment.

### For Non-Emergency Personnel

**Protective equipment:** Use appropriate personal protection equipment (PPE).

**Emergency procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective equipment:** Equip cleanup crew with proper protection.

**Emergency procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

**Environmental precautions**: Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

**Methods for cleaning up**: Place absorbed material in closed containers for disposal. Clean up spills immediately and dispose of waste safely. Notify authorities if product enters sewers or public waters.

**Methods for containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Further information: Refer to Section 8, Exposure Controls/Personal Protection. Refer to Section 13, Disposal Considerations.

### **SECTION 7: HANDLING AND STORAGE**

#### Precautions for safe handling:

**Additional hazards when processed:** Hazardous polymerization may occur if exposed to high temperature. Product to be handled in a closed system and under strictly controlled conditions.

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work.

#### **Conditions for safe storage:**

**Technical measures:** Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Comply with applicable regulations.

**Storage conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible materials:** Strong acids, strong bases, strong oxidizers. Nitrogen containing compounds, ammonium compounds.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters:** For substances listed in Section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

	<i>Quartz (14808</i>	<i>-60-7)</i>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
USA OSHA	OSHA PEL (STEL) (mg/m <sup>3</sup> )	250 mppcf/%SiO <sub>2</sub> +5, 10mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m³ (respirable particulate)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m³ (respirable fraction)
Nunavut	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m³ (respirable mass)
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m³ (respirable mass)
Ontario	OEL TWA (mg/m <sup>3</sup> )	0.10 mg/m³ (designated substances
		regulation-respirable)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	0.025 mg/m³ (respirable fraction)
Quebec	VEMP (mg/m <sup>3</sup> )	0.1 mg/m³ (respirable dust)
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable fraction)
Yukon	OEL TWA (mg/m <sup>3</sup> )	300 particle/mL
Triethylenetetramine (112-24-3)		
Ontario	OEL TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Ontario	OEL TWA (ppm)	0.5 ppm

#### **Exposure controls:**

Engineering controls: Emergency eyewash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

**Personal protective equipment:** Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection. Face shield.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)**

Hand protection: Wear chemically resistant protective gloves.

Eve protection: Chemical safety goggles.

Skin and body protection: Wear suitable protective clothing.

Respiratory protection: If exposure limits are exceeded or irritation is experienced, approved respiratory

protection should be worn.

Environmental exposure controls: Do not allow the product to be released into the environment.

Consumer exposure controls: Do not eat, drink or smoke during use.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical state Liquid

Appearance Thick liquid
Odor Amine odor

Odor threshold No data available

pH No data available

Melting point/freezing point

No data available

Initial boiling point & range

~350°F (176.67°C)

Flash point \$\frac{170.07}{200}\$ \text{C} \$\frac{170.07}{200}\$ \text{C} \$\frac{1}{2}0.07\$ \text{C}

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper flammable limit No data available

Lower flammable limit No data available

Vapor pressure No data available

Vapor density at 20 °C No data available

Relative density No data available

Solubility No data available

Auto-ignition temperature No data available

Decomposition Temperature No data available

Viscosity Approximately 30,000 cps

Partition coefficient (n-octanol/water)

No data available

Specific Gravity 1.4

Explosion data – sensitivity to mechanical impact Not expected to present an explosion hazard

due to mechanical impact.

Explosion data – sensitivity to static discharge Not expected to present an explosion hazard

due to static discharge.

### **SECTION 10: STABILITY AND REACTIVITY**

Conditions of reactivity: Hazardous polymerization can occur on heating.

**Incompatible materials:** Strong acids. Strong bases. Strong oxidizers. Amines.

Chemical stability: Stable under recommended handling and storage conditions (see Section 7).

Possibility of hazardous reactions: Hazardous polymerization will not occur.

Conditions to avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

**Hazardous decomposition product:** Under fire conditions this material may produce hazardous carbon dioxide (CO<sup>2</sup>), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides. Ammonia. Amines

### **SECTION 11: TOXICOLOGICAL INFORMATION**

### Information on Toxicological Effects - Product

Acute toxicity: Not classified

LD50 and LC50 data: No data available

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/irritation: Causes serious eye damage.

**Respiratory or skin sensitization:** May cause an allergic skin reaction.

Germ cell mutagenicity: Not classified

**Teratogenicity:** Not classified **Carcinogenicity:** Not classified

Specific target organ toxicity (repeated exposure): Not classified

Reproductive toxicity: Not classified

Specific target organ toxicity (single exposure): Not classified

Aspiration hazard: Not classified

Symptoms/Injuries after inhalation: May cause respiratory irritation

Symptoms/Injuries after skin contact: Contact may cause immediate severe irritation progressing quickly to chemical burns. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic reaction in sensitive individuals.

Symptoms/Injuries after eye contact: Serious damage to eyes. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Symptoms/Injuries after ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic symptoms: No data available

#### <u>Information on Toxicological Effects - Ingredients</u>

#### LD50 and LC50 data:

Quartz (14808-60-7)		
LD50 Oral Rat	>5000 mg/kg	
LD50 Dermal Rat	>5000 mg/kg	
Fatty acids, C18-unsaturated, dimer	s, polymers with tall-oil fatty acids and triethylenetetramine	
(68082-29-1)		
LD50 Oral Rat	>2000 mg/kg	
LD50 Dermal Rat	>2000 mg/kg	
Triethylenetetramine (112-24-3)		
LD50 Oral Rat	2500 mg/kg	
LD50 Dermal Rabbit	550 mg/kg	
2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)		
LD50 Oral Rat	1000 mg/kg	
LD50 Dermal Rat	1280 mg/kg	
Tetraethylenepentamine (112-57-2)		
LD50 Oral Rat	2100 mg/kg	
LD50 Dermal Rat	660 μl/kg	
Quartz (14808-60-7)		
IARC Group	Group 1	
National Toxicology Program (NTP) Status	Known Human Carcinogens	

### **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity:** Toxic to aquatic life with long lasting effects.

Triethylenetetramine (112-24-3)		
LC50 Fish 1	570 mg/l (exposure time: 96h – species: Poecilia reticulata [semi-static])	
EC50 Daphnia 1	31.1 mg/l (exposure time: 48h – species: Daphnia magna)	
LC50 Fish 2	495 mg/l (exposure time: 96h – species: Pimephales promelas)	
Tetraethylenepentamine (112-	57-2)	
LC50 Fish 1	420 mg/l (exposure time: 96h – species: Poecilia reticula [static])	
EC50 Daphnia 1	24.1 mg/l (exposure time: 48h - species: Daphnia magna)	

Persistence and degradability: No data available

# **SECTION 12: ECOLOGICAL INFORMATION (CONTINUED)**

#### Bioaccumulative potential:

Triethylenetetramine (112-24-3)		
BCF Fish 1	(no bioaccumulation expected)	
Log Pow	-1.4	
Tetraethylenepentamine (112-57-2)		
BCF Fish 1	(no bioaccumulation expected)	
Log Pow	<1	

Mobility in soil: No data available

Further information: Avoid release to the environment.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Disposal: Avoid release to the environment. Do not flush into surface water or sewer system.

**Further information:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

### **SECTION 14: TRANSPORT INFORMATION**

#### In accordance with DOT:

Proper shipping name: CORROSIVE LIQUIDS, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol, Tetraethylenepentamine)

Hazard class: 8
Identification number: UN1760
Label codes: 8

Packing group:

Marine pollutant: Marine pollutant

ERG number: 171
In accordance with IMDG:

Proper shipping name: CORROSIVE LIQUIDS, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol, Tetraethylenepentamine)

Hazard class: 8

Identification number: UN1760

Label codes: 8 Packing group: II

Marine pollutant: Marine pollutant

EmS-No. (Fire): F-A EmS-No. (Spillage): S-B

### In accordance with IATA:

Proper shipping name: CORROSIVE LIQUIDS, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol, Tetraethylenepentamine)

Hazard class: 8

Identification number: UN1760 Label codes: 8 Packing group: II ERG code (IATA): 8L



### In accordance with TDG:

Proper shipping name: CORROSIVE LIQUIDS, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol, Tetraethylenepentamine)

Hazard class: 8
Identification number: UN1760
Label codes: 8
Packing group: II

Marine pollutant: Marine pollutant

# **SECTION 15: REGULATORY INFORMATION**

# U.S. Federal regulations:

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
,	Delayed (chronic) health hazard	
Propanol, oxybis-, dibenzoate (27138-31-4)		
Listed on the United States Toxic Substances Control Act (TSC	A) inventory.	
Quartz (14808-60-7)		
Listed on the United States TSCA inventory.		
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine		
(68082-29-1)		
Listed on the United States TSCA inventory.		
Triethylenetetramine (112-24-3)		
Listed on the United States TSCA inventory.		
2,4,6-Tri(dimethylaminomethyl) phenol (90-72-2)		
Listed on the United States TSCA inventory.		
Tetraethylenepentamine (112-57-2)		
Listed on the United States TSCA inventory.		

### U.S. State regulations:

Quartz (14808-60-7)	
California Proposition 65 Carcinogens List	WARNING: This product contains chemicals known to the State
	of California to cause cancer.
Massachusetts	Right To Know List
New Jersey	Right To Know Hazardous Substances List
Pennsylvania	RTK (Right To Know) List
Triethylenetetramine (112-24-3)	
Massachusetts	Right To Know List
New Jersey	Right To Know Hazardous Substances List
Pennsylvania	RTK (Right To Know) List
Tetraethylenepentamine (112-57-2)	
Massachusetts	Right To Know List
New Jersey	Right To Know Hazardous Substances List
Pennsylvania	RTK (Right To Know) List

Canadian regulations:	
WHMIS Classification	Class D Division 2 Subdivision A – Very toxic material causing other toxic effects Class D Division 2 Subdivision B – Toxic material causing other toxic effects Class E – Corrosive material
Propanol, oxybis-, dibenzo	ate (27138-31-4)
Listed on the Canadian Domestic S	Substances List (DSL)
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria.
Quartz (14808-60-7)	
Listed on the Canadian DSL	
Listed on the Canadian Ingredient	Disclosure List (IDL)
IDL Concentration 1%	
WHMIS Classification	Class D Division 2 Subdivision A – Very toxic material causing other toxic effects
Fatty acids, C18-unsatura	ted, dimers, polymers with tall-oil fatty acids and triethylenetetramine
(68082-29-1)	
Listed on the Canadian DSL	
WHMIS Classification	Class D Division 2 Subdivision B – Toxic material causing other toxic effects
	Class E – Corrosive material
Triethylenetetramine (112	2-24-3)
Listed on the Canadian DSL	
Listed on the Canadian IDL	
IDL Concentration 0.1%	
WHMIS Classification	Class D Division 1 Subdivision B – Toxic material causing immediate and serious toxic effects
	Class D Division 2 Subdivision B – Toxic material causing other toxic effects
	Class E – Corrosive material

# **Section 15: Regulatory Information (Continued)**

### **Canadian regulations (Continued):**

2,4,6-Tri(dimethylamine	omethyl) phenol (90-72-2)
Listed on the Canadian DSL	
WHMIS Classification	Class D Division 2 Subdivision B – Toxic material causing other toxic effects
	Class E – Corrosive material
Tetraethylenepentamine	(112-57-2)
Listed on the Canadian DSL	
Listed on the Canadian IDL	
IDL Concentration 1%	
WHMIS Classification	Class D Division 1 Subdivision B – Toxic material causing immediate and serious toxic effects
	Class E – Corrosive material

WHMIS classification(s): see Canadian regulations.

**Further Information:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### **SECTION 16: OTHER INFORMATION**

### **GHS Full Text Phrases:**

Acute Tox. 4 (Dermal) Acute Tox. 4 (Oral)	Acute toxicity (dermal) Category 4 Acute toxicity (oral) Category 4 Hazardous to the aquatic environment – Acute Hazard Category 3
Acute Tox. 4 (Oral)	Hazardous to the aquatic environment – Acute Hazard Category 3
Aquatic Acute 3	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard Category 3
Carc. 1A	Carcinogenicity Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

#### **Further Information:**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Preparation Date:** 09/22/2015